ROCKSHIELD

CATALOGUE 2026

TRUCK & BUS TIRE



NEW PATTERNS · COMING SOON



SHIELD YOUR FORTUNE

ATA Smart Trading LLC

Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE

Phone: +971 58 585 5490

INDEX

CONTENTS

COMING SOON

RK606	315/80R22.5	04
RS601	315/80R22.5	05
RS617	385/65R22.5	06

ALL POSITION

RK661	1 SIZE	07
RK869	1 SIZE	08
RS613	1 SIZE	09
RS628	2 SIZES	10
RS63	1 SIZE	11
RS633	2 SIZES	12
RS634	3 SIZES	13
RS681	1 SIZE	14
RS696	10 SIZES	15
RS696+	2 SIZES	16
RS697	4 SIZES	17
RS697+	1 SIZE	18

STEER & TRAILER

RS603	1 SIZE	19
RS607	1 SIZE	20
RS612	2 SIZES	21
RS622	2 SIZES	22
RS632	1 SIZE	23
RS635	1 SIZE	24
RS637	10 SIZES	25
RS661	1 SIZE	26
RS662	1 SIZE	27
RS667	2 SIZES	28
RS682	1 SIZE	29
RS688	1 SIZE	30
RS698	2 SIZES	31
RS699	2 SIZES	32
RS862	1 SIZE	33
RS866	1 SIZE	34
RS898	3 SIZES	35

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

INDEX

CONTENTS

DRIVING

RK607	2 SIZES	36
RK609	1 SIZE	37
RK619	2 SIZES	38
RK623	1 SIZE	39
RK625	1 SIZE	40
RK627	1 SIZE	41
RK628	1 SIZE	42
RK629	1 SIZE	43
RK632	1 SIZE	44
RK635	2 SIZES	45
RK651	1 SIZE	46
RK653	2 SIZES	47
RK655	3 SIZES	48
RK668	4 SIZES	49
RK669	5 SIZES	50
RK677	2 SIZES	51
RK678	3 SIZES	52
RK686	2 SIZES	53
RK695	1 SIZE	54
RK699	4 SIZES	55
RK855	2 SIZES	56
RK868	2 SIZES	57
RK877	2 SIZES	58
RK878	1 SIZE	59
RKSW2	1 SIZE	60
RKSW3	1 SIZE	61
RS602	1 SIZE	62
RS623	1 SIZE	63
RS686	1 SIZE	64

Rock Shield Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

NEW PATTERN

RK606

COMING SOON

COMING SOON | TBR RADIAL | 1 SIZE

22
PLY RATING

274
TREAD WIDTH MM



274 mm

Wide tread width for strength, stability and long service life.

AVAILABLE SIZE

RK606 · COMING SOON

SIZE	PR	LOAD INDEX S | D	SPEED RATING	TREAD WIDTH
315/80R22.5	22	161/157	K	274 mm

Full technical data will be released at launch.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

NEW PATTERN

RS601

COMING SOON

COMING SOON | TBR RADIAL | 1 SIZE

22
PLY RATING

260
TREAD WIDTH MM



260 mm

Wide tread width for strength, stability and long service life.

AVAILABLE SIZE

RS601 · COMING SOON

SIZE	PR	LOAD INDEX S | D	SPEED RATING	TREAD WIDTH
315/80R22.5	22	161/157	K	260 mm

Full technical data will be released at launch.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

NEW PATTERN

RS617

COMING SOON

COMING SOON | TBR RADIAL | 1 SIZE

24
PLY RATING

310
TREAD WIDTH MM



310 mm

Wide tread width for strength, stability and long service life.

AVAILABLE SIZE

RS617 · COMING SOON

SIZE	PR	LOAD INDEX S | D	SPEED RATING	TREAD WIDTH
385/65R22.5	24	164	K	310 mm

Full technical data will be released at launch.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN


RK661

ALL POSITION RADIAL

ALL POSITION | TBR RADIAL | 1 SIZE

1	18	17
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK661 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
12R22.5	18	152/149	L	9.00	17.0	3550/3250	930	ALL POSITION

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN


RK869

ALL POSITION RADIAL

ALL POSITION | TBR RADIAL | 1 SIZE

1	18	19
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK869 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
12R22.5	18	152/149	L	9.00	19.0	3550/3250	930	ALL POSITION

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS613

ALL POSITION RADIAL

ALL POSITION | TBR RADIAL | 1 SIZE

1 SIZE

16 PLY RATING

12 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS613 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
7.50R16LT	16	125/121	L	6.00G	12.0	1650/1450	870	ALL POSITION

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS628

ALL POSITION RADIAL

ALL POSITION | TBR RADIAL | 2 SIZES

2 SIZES

20 PLY RATING

14.5–15 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS628 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
12.00R24	20	160/156	K	8.50	14.5	4500/4000	850	ALL POSITION
315/80R22.5	20	156/150	M	9.00	15.0	4000/3350	850	ALL POSITION

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS63

ALL POSITION RADIAL

ALL POSITION | TBR RADIAL | 1 SIZE

1	18	16.5
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS63 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11.00R20	18	152/149	K	8.00	16.5	3550/3250	930	ALL POSITION

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS633

ALL POSITION RADIAL

ALL POSITION | TBR RADIAL | 2 SIZES

2 SIZES

18–20 PLY RATING

17.5–18 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS633 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11R22.5	18	148/145	L	8.25	18.0	3150/2900	850	ALL POSITION
295/80R22.5	20	154/150	K	9.00	17.5	3750/3350	850	ALL POSITION

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS634

ALL POSITION RADIAL

ALL POSITION | TBR RADIAL | 3 SIZES

3 SIZES

18 PLY RATING

15–15.5 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS634 · 3 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
9.5R17.5	18	143/141	L	6.75	15.0	2725/2575	875	ALL POSITION
215/75R17.5	18	135/133	L	6.00	15.0	2180/2060	860	ALL POSITION
235/75R17.5	18	143/141	L	6.75	15.5	2725/2575	900	ALL POSITION

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS681

ALL POSITION RADIAL

ALL POSITION | TBR RADIAL | 1 SIZE

1	22	17
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS681 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
12.00R20	22	158/155	J	8.50	17.0	4250/3875	970	ALL POSITION

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS696

ALL POSITION RADIAL

ALL POSITION | TBR RADIAL | 10 SIZES



10 SIZES

14–20 PLY RATING

13–17.5 TREAD MM

RECOMMENDED VEHICLES



AVAILABLE SIZES & TECHNICAL DATA

RS696 · 10 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
7.50R16LT	14	122/118	L	6.00G	13.0	1500/1320	770	ALL POSITION
9.00R20	16	144/142	K	7.00	15.5	2800/2650	900	ALL POSITION
10.00R20	18	149/146	K	7.50	16.5	3250/3000	930	ALL POSITION
11.00R20	18	152/149	K	8.00	17.0	3550/3250	930	ALL POSITION
12.00R20	20	156/153	K	8.50	17.5	4000/3650	900	ALL POSITION
12.00R24	20	160/156	K	8.50	15.0	4500/4000	850	ALL POSITION
11R22.5	18	148/145	M	8.25	15.0	3150/2900	850	ALL POSITION
12R22.5	18	152/149	M	9.00	17.0	3550/3250	930	ALL POSITION
13R22.5	20	156/153	K	9.75	17.5	4000/3650	930	ALL POSITION
315/80R22.5	20	156/150	M	9.00	16.0	4000/3350	850	ALL POSITION

S = single · D = dual. Max. load and pressure per the technical data of each size. Always inflate to the tire pressure standard and match tires of the same pattern and specification on the same axle.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS696+

ALL POSITION RADIAL

ALL POSITION | TBR RADIAL | 2 SIZES

2 SIZES

18–20 PLY RATING

17–17.5 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS696+ · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11.00R20	18	152/149	K	8.00	17.0	3550/3250	930	ALL POSITION
12.00R20	20	156/153	K	8.50	17.5	4000/3650	900	ALL POSITION

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS697

ALL POSITION RADIAL

ALL POSITION | TBR RADIAL | 4 SIZES

4 SIZES

16–20 PLY RATING

15.5–17.5 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS697 · 4 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
9.00R20	16	144/142	K	7.00	15.5	2800/2650	900	ALL POSITION
10.00R20	18	149/146	K	7.50	16.5	3250/3000	930	ALL POSITION
11.00R20	18	152/149	K	8.00	17.0	3550/3250	930	ALL POSITION
12.00R20	20	156/153	K	8.50	17.5	4000/3650	900	ALL POSITION

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS697+

ALL POSITION RADIAL

ALL POSITION | TBR RADIAL | 1 SIZE



1	18	17
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES



AVAILABLE SIZES & TECHNICAL DATA

RS697+ · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11.00R20	18	152/149	K	8.00	17.0	3550/3250	930	ALL POSITION

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS603

STEER & TRAILER RADIAL

STEER & TRAILER | TBR RADIAL | 1 SIZE



1	18	18
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES



AVAILABLE SIZES & TECHNICAL DATA

RS603 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11R22.5	18	148/145	M	8.25	18.0	3150/2900	850	STEER & TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN


RS607

TRAILER RADIAL

TRAILER | TBR RADIAL | 1 SIZE

1	24	15
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS607 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
385/65R22.5	24	164	K	11.75	15.0	5000	900	TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS612

STEER & TRAILER RADIAL

STEER & TRAILER | TBR RADIAL | 2 SIZES



2 SIZES

18 PLY RATING

12.5–13 TREAD MM

RECOMMENDED VEHICLES



AVAILABLE SIZES & TECHNICAL DATA

RS612 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
265/70R19.5	18	143/141	K	7.50	12.5	2725/2575	850	STEER & TRAILER
285/70R19.5	18	150/148	K	8.25	13.0	3350/3150	900	STEER & TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS622

STEER & TRAILER RADIAL

STEER & TRAILER | TBR RADIAL | 2 SIZES



2	20–22	16.5–17
SIZES	PLY RATING	TREAD MM

RECOMMENDED VEHICLES



AVAILABLE SIZES & TECHNICAL DATA

RS622 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
295/80R22.5	20	154/150	K	9.00	17.0	3750/3350	850	STEER & TRAILER
315/80R22.5	22	158/156	K	9.00	16.5	4250/4000	900	STEER & TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN


RS632

STEER & TRAILER RADIAL

STEER & TRAILER | TBR RADIAL | 1 SIZE

1	20	15
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS632 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
315/80R22.5	20	156/150	M	9.00	15.0	4000/3350	850	STEER & TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS635

STEER & TRAILER RADIAL

STEER & TRAILER | TBR RADIAL | 1 SIZE



1	18	17
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES



AVAILABLE SIZES & TECHNICAL DATA

RS635 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11R22.5	18	148/145	L	8.25	17.0	3150/2900	850	STEER & TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS637

STEER & TRAILER RADIAL

STEER & TRAILER | TBR RADIAL | 10 SIZES



10 SIZES

16–18 PLY RATING

12–16 TREAD MM

RECOMMENDED VEHICLES



AVAILABLE SIZES & TECHNICAL DATA

RS637 · 10 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
9.5R17.5	18	143/141	L	6.75	13.5	2725/2575	875	STEER & TRAILER
11R22.5	18	148/145	M	8.25	13.5	3150/2900	850	STEER & TRAILER
11R24.5	18	149/146	M	8.25	13.5	3250/3000	830	STEER & TRAILER
215/75R17.5	18	135/133	L	6.00	12.0	2180/2060	860	STEER & TRAILER
235/75R17.5	18	143/141	L	6.75	13.0	2725/2575	900	STEER & TRAILER
245/70R19.5	18	144/142	J	7.50	13.5	2800/2650	900	STEER & TRAILER
255/70R22.5	16	140/137	M	7.50	14.0	2500/2300	830	STEER & TRAILER
275/70R22.5	18	146/143	L	8.25	14.0	3000/2725	900	STEER & TRAILER
275/80R22.5	18	149/146	M	8.25	14.0	3250/3000	900	STEER & TRAILER
295/80R22.5	18	152/149	M	9.00	16.0	3550/3250	900	STEER & TRAILER

S = single · D = dual. Max. load and pressure per the technical data of each size. Always inflate to the tire pressure standard and match tires of the same pattern and specification on the same axle.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS661

STEER & TRAILER RADIAL

STEER & TRAILER | TBR RADIAL | 1 SIZE



1	18	14.5
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES



AVAILABLE SIZES & TECHNICAL DATA

RS661 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11R22.5	18	148/145	M	8.25	14.5	3150/2900	850	STEER & TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS662

STEER & TRAILER RADIAL

STEER & TRAILER | TBR RADIAL | 1 SIZE




1 SIZE

18 PLY RATING

15 TREAD MM

RECOMMENDED VEHICLES



AVAILABLE SIZES & TECHNICAL DATA

RS662 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
12R22.5	18	152/149	M	9.00	15.0	3550/3250	930	STEER & TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS667

STEER & TRAILER RADIAL


STEER & TRAILER | TBR RADIAL | 2 SIZES

2 SIZES

20–22 PLY RATING

15.5–16.5 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS667 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
315/70R22.5	20	154/151	L	9.00	15.5	3750/3450	930	STEER & TRAILER
315/80R22.5	22	161/157	K	9.00	16.5	4250/4000	900	STEER & TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS682

STEER & TRAILER RADIAL

STEER & TRAILER | TBR RADIAL | 1 SIZE

1	20	14.5
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS682 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
12.00R24	20	160/156	K	8.50	14.5	4500/4000	850	STEER & TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN


RS688

TRAILER RADIAL

TRAILER | TBR RADIAL | 1 SIZE

1	24	14.5
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS688 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
385/65R22.5	24	164	K	11.75	14.5	5000	900	TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS698

STEER & TRAILER RADIAL


STEER & TRAILER | TBR RADIAL | 2 SIZES

2 SIZES

20–24 PLY RATING

14.5 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS698 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
385/55R22.5	20	160	K	12.25	14.5	4500	900	STEER & TRAILER
385/65R22.5	24	164	K	11.75	14.5	5000	900	STEER & TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS699

STEER & TRAILER RADIAL

STEER & TRAILER | TBR RADIAL | 2 SIZES

2 SIZES

18 PLY RATING

16–16.5 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS699 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11R22.5	18	146/143	M	8.25	16.0	3000/2725	830	STEER & TRAILER
12R22.5	18	152/149	M	9.00	16.5	3550/3250	930	STEER & TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS862

STEER & TRAILER RADIAL


STEER & TRAILER | TBR RADIAL | 1 SIZE

1 SIZE

18 PLY RATING

15 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS862 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
315/70R22.5	18	152/148	M	9.00	15.0	3550/3150	830	STEER & TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS866

STEER & TRAILER RADIAL

STEER & TRAILER | TBR RADIAL | 1 SIZE



1	18	15
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES



AVAILABLE SIZES & TECHNICAL DATA

RS866 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11.00R20	18	152/149	K	8.00	15.0	3550/3250	930	STEER & TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS898

STEER & TRAILER RADIAL

STEER & TRAILER | TBR RADIAL | 3 SIZES



3 SIZES

18–20 PLY RATING

15 TREAD MM

RECOMMENDED VEHICLES



AVAILABLE SIZES & TECHNICAL DATA

RS898 · 3 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11R22.5	18	148/145	M	8.25	15.0	3150/2900	850	STEER & TRAILER
295/80R22.5	18	152/149	M	9.00	15.0	3550/3250	900	STEER & TRAILER
315/80R22.5	20	156/150	M	9.00	15.0	4000/3350	850	STEER & TRAILER

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK607

DRIVING RADIAL

DRIVING | TBR RADIAL | 2 SIZES

2 SIZES

18–20 PLY RATING

23 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK607 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11.00R20	18	152/149	K	8.00	23.0	3550/3250	930	DRIVING
12.00R20	20	156/153	K	8.50	23.0	4000/3650	900	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK609

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	18	23
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK609 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11.00R20	18	152/149	E	8.00	23.0	3550/3250	930	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK619

DRIVING RADIAL

DRIVING | TBR RADIAL | 2 SIZES

2 SIZES

18–20 PLY RATING

21.5 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK619 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11.00R20	18	152/149	E	8.00	21.5	3550/3250	930	DRIVING
12.00R20	20	156/153	E	8.50	21.5	4000/3650	900	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK623

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	18	20
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK623 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
295/80R22.5	18	152/149	L	9.00	20.0	3550/3250	900	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN


RK625

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	18	24
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK625 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
12R22.5	18	152/149	J	9.00	24.0	3550/3250	930	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN


RK627

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	18	22.5
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK627 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
12R22.5	18	152/149	J	9.00	22.5	3550/3250	930	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK628

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	18	21.5
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK628 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11R22.5	18	148/145	M	8.25	21.5	3150/2900	850	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK629

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	22	24
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK629 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
12.00R20	22	158/155	E	8.50	24.0	4250/3875	970	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK632

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	22	26
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK632 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
12.00R20	22	158/155	E	8.50	26.0	4250/3875	970	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK635

DRIVING RADIAL

DRIVING | TBR RADIAL | 2 SIZES

2 SIZES

18 PLY RATING

19.5 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK635 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11R22.5	18	148/145	M	8.25	19.5	3150/2900	850	DRIVING
11R24.5	18	149/146	M	8.25	19.5	3250/3000	830	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN


RK651

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	20	20.5
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK651 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
13R22.5	20	156/153	K	9.75	20.5	4000/3650	930	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK653

DRIVING RADIAL

DRIVING | TBR RADIAL | 2 SIZES

2 SIZES

18 PLY RATING

15.5–16 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK653 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
215/75R17.5	18	135/133	L	6.00	15.5	2180/2060	860	DRIVING
235/75R17.5	18	143/141	L	6.75	16.0	2725/2575	900	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK655

DRIVING RADIAL

DRIVING | TBR RADIAL | 3 SIZES

3	18	15–22.5
SIZES	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK655 · 3 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
9.5R17.5	18	143/141	L	6.75	15.0	2725/2575	875	DRIVING
11R22.5	18	148/145	M	8.25	21.5	3150/2900	850	DRIVING
12R22.5	18	152/149	L	9.00	22.5	3550/3250	930	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK668

DRIVING RADIAL

DRIVING | TBR RADIAL | 4 SIZES

4 SIZES

16–20 PLY RATING

20 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK668 · 4 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11R22.5	16	146/143	L	8.25	20.0	3000/2725	830	DRIVING
12R22.5	18	152/149	L	9.00	20.0	3550/3250	930	DRIVING
295/80R22.5	18	152/149	L	9.00	20.0	3550/3250	900	DRIVING
315/80R22.5	20	156/150	L	9.00	20.0	4000/3350	850	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK669

DRIVING RADIAL

DRIVING | TBR RADIAL | 5 SIZES

5 SIZES

18–22 PLY RATING

15.5–24.5 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK669 · 5 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
9.5R17.5	18	143/141	L	6.75	15.5	2725/2575	875	DRIVING
215/75R17.5	18	135/133	L	6.00	15.5	2180/2060	860	DRIVING
235/75R17.5	18	143/141	L	6.75	15.5	2725/2575	900	DRIVING
315/70R22.5	20	154/151	K	9.00	20.0	3750/3450	930	DRIVING
315/80R22.5	22	158/156	K	9.00	24.5	4250/4000	900	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK677

DRIVING RADIAL

DRIVING | TBR RADIAL | 2 SIZES

2	20–24	22–26
SIZES	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK677 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
295/80R22.5	20	154/150	F	9.00	22.0	3750/3350	850	DRIVING
315/80R22.5	24	170/167	F	9.00	26.0	6000/5450	970	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK678

DRIVING RADIAL

DRIVING | TBR RADIAL | 3 SIZES

3 SIZES

18 PLY RATING

15–20 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK678 · 3 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
265/70R19.5	18	143/141	K	7.50	15.0	2725/2575	850	DRIVING
285/70R19.5	18	150/148	K	8.25	16.0	3350/3150	900	DRIVING
315/70R22.5	18	152/148	M	9.00	20.0	3550/3150	830	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN


RK686

DRIVING RADIAL

DRIVING | TBR RADIAL | 2 SIZES

2	18–20	18–20
SIZES	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK686 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
12R22.5	18	152/149	L	9.00	18.0	3550/3250	930	DRIVING
315/80R22.5	20	156/150	L	9.00	20.0	4000/3350	850	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN


RK695

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	20	20
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK695 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
315/70R22.5	20	154/151	L	9.00	20.0	3750/3450	930	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK699

DRIVING & ALL POSITION RADIAL

DRIVING & ALL POSITION | **TBR RADIAL** | **4 SIZES**



4	14–20	15.5–19
SIZES	PLY RATING	TREAD MM

RECOMMENDED VEHICLES



AVAILABLE SIZES & TECHNICAL DATA

RK699 · 4 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
7.50R16LT	14	122/118	L	6.00G	15.5	1500/1320	770	DRIVING
8.25R16LT	16	128/124	L	6.50H	16.0	1800/1600	770	DRIVING
11.00R20	18	152/149	K	8.00	19.0	3550/3250	930	ALL POSITION
12.00R20	20	156/153	K	8.50	19.0	4000/3650	900	ALL POSITION

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK855

DRIVING RADIAL

DRIVING | TBR RADIAL | 2 SIZES

2	20–22	21–23
SIZES	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK855 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
295/80R22.5	20	154/150	K	9.00	21.0	3750/3350	850	DRIVING
315/80R22.5	22	158/156	K	9.00	23.0	4250/4000	900	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK868

DRIVING RADIAL

DRIVING | TBR RADIAL | 2 SIZES

2 SIZES

18–20 PLY RATING

19 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK868 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11.00R20	18	152/149	K	8.00	19.0	3550/3250	930	DRIVING
12.00R20	20	156/153	K	8.50	19.0	4000/3650	900	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RK877

DRIVING RADIAL

DRIVING | TBR RADIAL | 2 SIZES

2 SIZES

18–22 PLY RATING

22–23 TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK877 · 2 SIZES

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11R22.5	18	148/145	L	8.25	23.0	3150/2900	850	DRIVING
315/80R22.5	22	158/156	K	9.00	22.0	4250/4000	900	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN


RK878

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	22	22
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RK878 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
315/80R22.5	22	158/156	J	9.00	22.0	4250/4000	900	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RKSW2

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	18	23
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RKSW2 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11R22.5	18	148/145	L	8.25	23.0	3150/2900	850	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RKSW3

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	18	21
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RKSW3 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11R22.5	18	148/145	L	8.25	21.0	3150/2900	850	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS602

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	18	23.5
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS602 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11R22.5	18	148/145	L	8.25	23.5	3150/2900	850	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS623

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	18	23
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS623 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11R22.5	18	148/145	L	8.25	23.0	3150/2900	850	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490

PATTERN

RS686

DRIVING RADIAL

DRIVING | TBR RADIAL | 1 SIZE

1	18	16
SIZE	PLY RATING	TREAD MM

RECOMMENDED VEHICLES





AVAILABLE SIZES & TECHNICAL DATA

RS686 · 1 SIZE

SIZE	PR	LOAD INDEX S | D	SPEED Rating	RIM	TREAD Depth (mm)	MAX. LOAD (kg) S | D	PRESSURE (kPa)	POSITION
11.00R20	18	152/149	K	8.00	16.0	3550/3250	930	DRIVING

01

Keep the air pressure normal. Inflate to the tire pressure standard.

02

Tire overload is strictly prohibited.

03

Install tires of the same brand, specification and level on the same axle.

S = single · D = dual. Max. load and pressure per the technical data of each size.

ATA Smart Trading LLC
Shop no 13, Al Maktoum Hospital Road, Deira, Dubai, UAE
Phone: +971 58 585 5490



ROCKSHIELD

SHIELD YOUR FORTUNE

ATA Smart Trading LLC

Shop no 13, Al Maktoum Hospital Road

Deira, Dubai, UAE

Phone: +971 58 585 5490